

# WIRELESS AC CURRENT METER SENSOR WITH EXTERNAL ANTENNA AND EXTERNAL CT SENSOR



## INFORMATION

Format	AC Powered
Frequency	868 MHz

Xemote wireless AC Current Meters measure the RMS current of an alternating current (AC) system using a current transformer (CT) that wraps around the "hot" wire of a two wire (hot, common, ground(optional)) power system. The sensor reports Minimum RMS current, maximum RMS current, average RMS current, and amp hours to the Xemote web portal. The Xemote portal system can generate watt hour or kilowatt hour readings as well.

## HIGHLIGHTS

- Up to 128 sensors connected to a single gateway
- ISM band wireless
- Critical Data Recovery (CDR) feature, 21 days at 10 min
- Non-intrusive installation

## APPLICATIONS

- Current Monitoring
- Current Usage
- Amp Hour Meter
- Watt/Kilowatt Hour Meter
- Equipment On/Off status

## SENSOR SPECIFICATIONS

### AC Current Meter

Absolute Max CT Current	100 A
Dielectric Strength	1000 Vac for 1 minute
Fire Resistance	UL94 – Vo
Measurement Resolution	12 Bits
Non – Linearity of sensor	± 3% (10% -120% of the rated input current range)
CT Sensor loom length	900mm
Other	Other CT sensor options are available 5A, 10A,15A, 20A, 25A, 30A, 50A and 60A

### Coin Cell

Battery Type	CR2450
Classification	Lithium Coin
Typical Capacity	620mAh
Dimensions	24.5mm x 5.0mm
Max Operating Temperature	-20 °C to +60 °C
Optimal Battery Operating Temperature	+10 °C to +50 °C
Supply Voltage	2.0 - 3.6 V
Battery Life	At 10-minute heartbeat setting, coin cell battery will typically last ~ 4 years (battery life is determined by sensor reporting frequency and other variables)

### Wireless

For more information about our products, please contact our sales department.

Visit our website at [www.xemote.co.za](http://www.xemote.co.za) | [sales@xemote.co.za](mailto:sales@xemote.co.za)

Copyright © 2019 Xemote (Pty) Ltd. All Rights Reserved.

Rev 1.0.0

# WIRELESS AC CURRENT METER SENSOR WITH EXTERNAL ANTENNA AND EXTERNAL CT SENSOR



Frequency	868 MHz Operating Frequency
Range	250 - 300 m non-line-of-sight device range (actual range may vary depending on environment). Longer ranges available with GSM Gateway 868Mhz outdoor Omni antenna 6dB gain.
Security	Encrypted
Certifications	ETSI EN 300 220-2 V2.4.1 (2012-05)
Antenna	Right angle or Straight angle on request
<b>I/O</b>	
Bidirectional IO Ports	2x Internal Input/output
Logic Level	3.3 V
Drive Current	20 mA Max
<b>Mechanical</b>	
Dimensions	115 mm x 64 mm x 31 mm 138 mm x 64 mm x 31 mm – Including flanges
Weight	245g including antenna
Material	ABS Plastic
Mounting Options	Wall mount flanges, button magnet, Velcro strips, double sided tape
IP Rating	IP54 (protection against the access of dust and splashing water)
<b>Environmental</b>	
Max Operating Temperature	-25 °C to +70 °C
<b>Warranty Terms</b>	
Period	12 months

## ORDERING INFORMATION

Part Number	Details	Configuration
XEMT4-20121	Sensor, Current Transformer (CT), SMA	Supplied with 1x CR2450 coin cell battery and right-angle antenna and 900mm length CT cable. Longer CT cable lengths available on request Straight angle antenna on request
5A, 10A,15A, 20A, 25A, 30A, 50A, and 60A	CT Options	

*Product images are for illustrative purposes only and may differ from the actual product.  
Specifications are subject to change without notice.*